Network Management & Monitoring

Log Management

Log Management and Monitoring

What is log management and monitoring?

- Keeping your logs in a secure place where they can be easily inspected.
- Watching your log files.
- They contain important information:
  - Lots of things happen and someone needs to review them.
  - It's not practical to do this manually.

Log Management and Monitoring

On your routers and switches

```
ep  1 04:40:11.788 INDIA: %SEC-6-IPACCESSLOGP: list 100 denied tcp
79.210.84.154(2167) -> 169.223.192.85(6662), 1 packet

ep  1 04:42:35.270 INDIA: %SYS-5-CONFIG_I: Configured from console
by pr on vty0 (203.200.80.75)

CI-3-TEMP: Overtemperature warning

ar  1 00:05:51.443: %LINK-3-UPDOWN: Interface Serial1, changed
state to down
```

And, your servers

```
ug 31 17:53:12 ubuntu nagios3: Caught SIGTERM, shutting down...

ug 31 19:19:36 ubuntu sshd[16404]: Failed password for root from
169.223.1.130 port 2039 ssh2
```

Log Management

- Centralize and consolidate log files
- Send all log messages from your routers, switches and servers to a single node – a *log server*.
- All network hardware and UNIX/Linux servers can be monitored using *syslog*.
- Windows can, also, use syslog using extra tools.
- Save logs locally, but, also, save them to a central log server.

Centralized logging



Configuring centralized logging

Cisco hardware

- At a minimum:
  - logging ip.of.logging.host

Unix and Linux nodes

- In /etc/syslog.conf, add:

```
*.*          @ip.of.log.host
```

- Restart syslogd

Other equipment have similar options

- Options to control *facility* y *level*

Receiving syslog messages

- Identify the *facility* that the equipment is going to use to send its messages.
- Reconfigure *syslogd* to listen to the network.
  - Ubuntu: add "`-r`" to `/etc/defaults/syslogd`
- Add an entry to *syslodg* where messages are going to be written:

```
local7.*                /var/log/routers
```

- Create the file

```
touch /var/log/routers
```

- Restart *syslogd*

```
/etc/init.d/syslogd restart
```

Syslog basics

Uses UDP protocol, port 514

- Syslog message have two attributes (in addition to the message itself):

Facility			Level	
Auth	Security	|	Emergency	(0)
Authpriv	User	|	Alert	(1)
Console	Syslog	|	Critical	(2)
Cron	UUCP	|	Error	(3)
Daemon	Mail	|	Warning	(4)
Ftp	Ntp	|	Notice	(5)
Kern	News	|	Info	(6)
Lpr		|	Debug	(7)
Local0 ...Local7		|		

Grouping logs

- Using *facility* and *level* you can group by category in distinct files.
- With software such as *syslog-ng* you can group by machine, date, etc. automatically in different directories.
- You can use *grep* to review logs.
- You can use typical UNIX tools to group and eliminate items that you wish to filter:

```
egrep -v '(list 100 denied|logging rate-limited)' mylogfile
```

- Is there a way to do this automatically?

SWATCH

Simple Log Watcher

- Written in Perl
- Monitors logs looking for patterns using regular expressions.
- Executes a specific action if a pattern is found.
- Can be any pattern and any action.
- Defining the patterns is the hard part.

Sample configuration

```
ignore /things to ignore/

watchfor /NATIVE_VLAN_MISMATCH/
        mail=root,subject=VLAN problem
        threshold type=limit,count=1,seconds=3600

watchfor /CONFIG_I/
        mail=root,subject=Router config
        threshold type=limit,count=1,seconds=3600
```

What are these? What does it mean?

References

http://www.loganalysis.org/

Syslog NG

- http://www.balabit.com/network-security/syslog-ng/

Windows Event Log a Syslog:

- https://engineering.purdue.edu/ECN/Resources/Documents/UNIX/evtsys

SWATCH log watcher

- http://swatch.sourceforge.net/
- http://www.loganalysis.org/sections/signatures/log-swatch-skendrick.txt
- http://www.loganalysis.org/
- http://sourceforge.net/docman/display_doc.php?docid=5332&group_id=25401

References cont.

- http://www.crypt.gen.nz/logsurfer
- http://sial.org/howto/logging/swatch/
- http://www.occam.com/sa/CentralizedLogging2009.pdf
- http://ristov.users.sourceforge.net/slct/

Questions?

?